




and its DESIGN are Proprietary to LEITNER-PDPA of AMERICA • Duplication without the Permission of LEITNER-PDPA of AMERICA is Prohibited

PROFILE DATA

LEFT MODEL:	COMP	INITIAL	FINAL
NOTATION:	UW	5.00 m/s	5.00 m/s
CARRIER TYPE:	4x4 Chair	CAPACITY UP: 1800.00 gph	2400.00
SCRIP TYPE:	RECHARGE	CAPACITY DOWN: 10.00 t	10.00 t
CABLE DIAMETER:	40.00 mm	SPACING:	45.00 m
SLOPE LENGTH:	179.17 m	INTERVAL:	0.00 sec
VERT. DIST:	39.37 m	CARRIERS:	90
COVER/VERAGE GRADE:	23.10 t	TRIP TIME:	5.76 min
LINE GAUGE:	4.00 m	TRENSION PRESSURE:	90.00 bars
DRIVE LOCATION:	TOP	TENSION FORCE:	18000.00 daN
TENSION LOCATION:	BOTTOM	ORIGIN OF SURVEY:	Area Type

DRAWN BY: R. Sheppardson		C52356fc		CHECKED BY:	
DATE: August 2004				SCALE: 1/1000 1/100	

[illegible]