

KEYNOTE LEGEND	
#	DESCRIPTION
402	OVERHEAD DOOR
404	4"x4" CONCRETE CURB
407	MOP SINK
408	SHELVES
411	8" CMU - SEALED FINISH, U.N.O.
412	6" CMU - SEALED FINISH, U.N.O.
413	(2) 75 GALLON WATER HEATERS - SEE PLUMBING DRAWINGS
414	12"x10" ALUMINUM VENT, TYP.
415	ATTIC ACCESS
416	SHOWER BENCH, TYP. SEE DETAILS 7 & 12/A501
417	FOLDING, ACCESSIBLE SHOWER BENCH
418	ELECTRICAL PANEL
420	UTILITY SHELF
427	PLASTIC TRIM, PAINTED - SEE DETAIL 10/A502
428	PLASTIC TRIM, PAINTED - SEE DETAIL 9/A502, TYP. @ ALL SHOWER ROOMS
429	WATER CHLORINE MONITOR BY OTHERS. PROVIDE 2" CONDUIT FOR SOLAR POWER ELECTRICAL LINES FROM ROOF. COORDINATE WITH WATER PROJECT CONTRACTOR
430	FOR PENETRATIONS OF SOLAR PANEL SUPPORT/CONDUIT PROVIDE FLASHING BOOT, SEE DETAIL 6/A501. COORDINATE LOCATION AND SIZE WITH WATER PROJECT CONTRACTOR
501	CONTROL JOINT
502	EXPANSION JOINT
503	EXPOSED TOP OF FOUNDATION
504	SHAPE FINISH SLAB TO FLOOR DRAIN
506	4" CONC. CURB, TYP. @ SHOWERS
507	EXTERIOR SLAB TO BE 4" THICK CONC. ON 6" GRAVEL BASE WHICH SHALL DAYLIGHT TO EXPOSED DRAINAGE AREA
601	RIDGE VENT - SEE DETAIL 11/A501
801	24 GAUGE STANDING SEAM METAL ROOF. FOR ROOF PENETRATIONS SEE DETAIL 6/A501



