



# PRO-STIK SEALANT

Providing products and services that protect our planet's clean water supply.



## PREFORMED JOINT SEALANT MADE OF BUTYL RUBBER MATERIAL IN FLEXIBLE ROPE FORM

PRO-STIK comes with a coated, protective release paper, that removes easily.

### TYPICAL APPLICATIONS

- \* Excellent Low Pressure, Water Resistant Joint Seal
- \* Manhole Joints and Vertical Risers
- \* Sanitary and Storm Sewer Manholes
- \* Sealing of Irrigation and Drainage Systems Joints
- \* Septic Tanks
- \* Box Culverts
- \* Underground (Utility) Vault Seal
- \* Burial Vaults
- \* Round and Special Shaped Pipe
- \* Architectural Foundation Joints
- \* Used with O-Rings for Extra Security in Pressure Pipe Joints
- \* Wet Wells

Meets and or exceeds all requirements of ASTM C-990 including section 6.2.1, Butyl rubber sealants. Butyl rubber sealants out perform mastic materials, for only pennies more. Contact us for samples and learn about the differences.



**PRESS-SEAL GASKET CORPORATION**

P.O. Box 10482, Fort Wayne, Indiana 46852

Phone: (260) 436-0521 (800) 348-7325 Fax: (260) 436-1908 E-mail: [sales@press-seal.com](mailto:sales@press-seal.com) Web: [www.press-seal.com](http://www.press-seal.com)

## BENEFITS

- \* PRO-STIK meets or exceeds all requirements of ASTM C-990 and AASHTO M-198.
- \* Made of high quality rubber, 98% solids that will not harden, shrink or oxidize.
- \* Good adhesion to dry concrete, all commonly specified concrete coatings, steel, glass, wood or painted surfaces.
- \* Extruded in rectangular shapes for optimal adhesion during application.
- \* Provided in rolls on coated release paper for easy installation in adverse weather conditions.
- \* Service life is indefinite with excellent resistance to acid and alkaline conditions.
- \* Cohesive properties allow for joint deflection or settlement without stringing or separating.
- \* Completely compatible for use in conjunction with rubber O-Ring designs.
- \* Extremely low moisture vapor transmission rate (MVTR).
- \* Special primers available for use on damp, contaminated, or difficult surfaces.

## AVAILABLE SIZES

**1/2"**  
.45 x .45

**1/2" x 3/4"**  
.75 x .50

**3/4"**  
.60 x .80

**1"**  
.75 x .105

**1 1/4"**  
.88 x 1.4

Round Equivalent Size x Length	Rolls Per Carton
1/2" x 26.4'	12
1/2" x 3/4" x 21.75'	8
3/4" x 14.5'	8
1" x 14.5'	6
1-1/4" x 14.5'	5

All sizes sold 40 cartons per pallet, except for the 1/2" x 26.4' which is 24 cartons per pallet. All pallets are shrink wrapped for outside storage.

Our Customer Service Department negotiates to obtain the lowest possible freight costs and passes the saving on to you, the customer.

Contact our Customer Service Department, or your Territory Manager, for information on our quantity discounts.

Copyright 1994 Press-Seal Gasket Corporation

Press-Seal believes all information is accurate as of its publication date. Information, specifications, and prices are all subject to change without notice. Press-Seal is not responsible for any inadvertent errors.



**PRESS-SEAL GASKET CORPORATION**

P.O. Box 10482, Fort Wayne, Indiana 46852

Phone: (260) 436-0521 (800) 348-7325 Fax: (260) 436-1908 E-mail: sales@press-seal.com Web: www.press-seal.com