
VEC



BMP: Concrete Waste Management

OBJECTIVES

CWM

☐ Housekeeping Practices ☑ Contain Waste ☐ Minimize Disturbed Areas ☐ Stabilize Disturbed Areas □ Protect Slopes/Channels

☐ Control Site Perimeter ☐ Control Internal Erosion

DESCRIPTION:

Prevent or reduce the discharge of pollutants to storm water from concrete waste by conducting washout off-site, performing on-site washout in a designated area, and training employees and subcontractors.

APPLICATIONS:

This technique is applicable to all types of sites.

INSTALLATION/APPLICATION CRITERIA:

- Store dry and wet materials under cover, away from drainage areas.
- Avoid mixing excess amounts of fresh concrete or cement on-site. Perform washout of concrete trucks off-site or in designated areas only.
- Do not wash out concrete trucks into storm drains, open ditches, streets, or
- Do not allow excess concrete to be dumped on-site, except in designated
- When washing concrete to remove fine particles and expose the aggregate, avoid creating runoff by draining the water within a bermed or level area. (See Earth Berm Barrier information sheet.)
- Train employees and subcontractors in proper concrete waste management.

Off-site washout of concrete wastes may not always be possible.

MAINTENANCE:

- Inspect subcontractors to ensure that concrete wastes are being properly
- If using a temporary pit, dispose hardened concrete on a regular basis.

TARGETED POLLUTANTS


□ Sediment □ Nutrients ☐ Toxic Materials □ Oil & Grease ☐ Floatable Materials

☑ Other Waste

M High Impact Medium Impact

☐ Low or Unknown Impact

- IMPLEMENTATION REQUIREMENTS
- □ Capital Costs □ O&M Costs ☑ Maintenance ☑ Training
- High ☑ Medium ☐ Low



BMP: Vehicle And Equipment Cleaning

DESCRIPTION:

MCNEIL ENGINEERING STRUCTURAL, L.C.

Prevent or reduce the discharge of pollutants to stormwater from vehicle and equipment washing and steam cleaning by using off-site facilities, washing in designated, contained areas only, eliminating discharges to the storm drain by infiltrating or recycling the wash water, and training employees and subcontractors.

APPROACH:

- Use off-site commercial washing and steam cleaning businesses as much as possible. Washing vehicles and equipment outdoors or in areas where wash water flows onto paved surfaces or into drainage pathways can pollute stormwater. If you wash a large number of vehicles or pieces of equipment, consider conducting this work at an off-site commercial business. These businesses are better equipped to handle and dispose of the wash waters properly. Performing this work off-site can also be economical by eliminating the need for a separate washing operation at your site.
- If washing must occur on-site, use designated, bermed wash areas to prevent wash water contact with stormwater, creeks, rivers, and other water bodies. The wash area can be sloped for wash water collection and subsequent infiltration into the ground.
- Use as little water as possible to avoid having to install erosion and sediment controls for the wash area. Use phosphate-free biodegradable soaps. Educat employees and subcontractors on pollution prevention measures. Do not permit steam cleaning on-site. Steam cleaning can generate significant pollutant concentrations.

- Even phosphate-free, biodegradable soaps have been shown to be toxic to fis before the soap degrades.
- Sending vehicles/equipment off-site should be done in conjunction with
- Stabilized Construction Entrance. (See BMP in the Construction Section). The measures outlined in this fact sheet are insufficient to address all the environmental impacts and compliance issues related to steam cleaning.

MAINTENANCE:

MCNEIL ENGINEERING STRUCTURAL, L.C

Minimal, some berm repair may be necessary.

APPLICATIONS

□ Manufacturing ☐ Material Handling ☑ Vehicle Maintenance ☑ Construction ☑ Commercial Activities □ Roadways ■ Waste Containment ☑ Housekeeping Practices

TARGETED POLLUTANTS

- Sediment
- Nutrients Heavy Metals
- Toxic Materials Oxygen Demanding Substances Oil & Grease ☐ Floatable Materials

■ High Impact

☐ Bacteria & Viruses

Medium Impact Low or Unknown Impact

IMPLEMENTATION REQUIREMENTS

☒ Capital Costs O&M Costs ☐ Maintenance ☑ Training

■ High ☑ Medium ☐ Low

- **OBJECTIVES**
- ☑ Housekeeping Practices
- ☐ Contain Waste
- Stabilize Disturbed Areas ☐ Protect Slopes/Channels ☐ Control Site Perimeter

□ Control Internal Erosion

DESCRIPTION:

BMP: Dust Controls

Dust control measures are used to stabilize soil from wind erosion, and reduce dust by construction activities.

APPLICATION:

Dust control is useful in any process area, loading and unloading area, material handling areas, and transfer areas where dust is generated. Street sweeping is limited to areas that are paved.

INSTALLATION/APPLICATION CRITERIA:

- Mechanical dust collection systems are designed according to the size of dust particles and the amount of air to be processed. Manufacturers'
- recommendations should be followed for installation (as well as the design of the equipment).
- Two kinds of street weepers are common: brush and vacuum. Vacuum sweepers

 Toxic Materials are more efficient and work best when the area is dry.
- Mechanical equipment should be operated according to the manufacturers' recommendations and should be inspected regularly.

- Is generally more expensive than manual systems.
- May be impossible to maintain by plant personnel (the more elaborate
- Is labor and equipment intensive and may not be effective for all pollutants (street sweepers).

If water sprayers are used, dust-contaminated waters should be collected and taker for treatment. Areas will probably need to be resprayed to keep dust from spreading.

TARGETED POLLUTANTS

■ Sediment □ Nutrients

□ Oil & Grease

☑ Medium Impact ☐ Low or Unknown Impact

IMPLEMENTATION REQUIREMENTS

☑ Capital Costs □ O&M Costs ☑ Maintenance

☐ Floatable Materials ☐ Other Waste

■ High Impact

☑ Trainina

■ High ☑ Medium ☐ Low

STA E E OGDEN UTAH WEBER I 4080 WEST 900 S WEST WEBER, UT

Church

PROPERTY NO: 502-2681

SHEET TITLE **SWPPP DETAILS**

C4.03

MCNEIL ENGINEERING - SURVEYING, L.C.

MCNEIL ASPEN CONSULTANTS, L.C.

PROJECT NO: 11358 CAD DWG. FILE: 11358-site.dwg

DESIGNED BY: NMD

FIELD CREW: NMD/MGS

MAY 2012