POWDER MOUNTAIN LOT 143R CONSTRUCTION DRAWINGS

Located in Sec 01 T7N R1E

Weber County, Utah



SHEET INDEX

COVER SHEET
GENERAL NOTES AND LEGEND
SITE AND HORIZONTAL CONTROL PLAN
CZ00
GRADING PLAN
CJ00
CUT FILL ANALYSIS
CJ01
UTILITY PLAN
C400
EROSION CONTROL PLAN
DETAILS
C700
DETAILS
C701
DETAILS
C702
DETAILS
C703

PLAN REVIEW ACCEPTANCE


FOR COMPLIANCE WITH THE APPLICABLE CONSTRUCTION CODES IDENTIFIED BELOW.

| BUILDING | STRUCTURAL | PLUMBING | ELECTRICAL | ENERGY | FIRE

PLAN REVIEW ACCEPTANCE OF DOCUMENTS DOES NOT AUTHORIZE CONSTRUCTION TO PROCEED IN VIOLATION OF ANY FEDERAL, STATE, OR LOCAL REGULATIONS.

BY: MEM | DATE: 07/11/18

WEST COAST CODE CONSULTANTS, INC.



POWDER MOUNTAIN HOUSE TOM BUTTGEN BACH 8645 EASET COPPER CREST EDEN, UT 84310

5530 CORBIN AVE. SUITE 300

WWW.SHAMIMENGINEERING.COM

TARZANA, CA 91356

(818) 788-6778

ARCHITECT:
TOM WISCOMBE
ARCHITECTURE

LOS ANGELES, CA 90057

WWW.TOMWISCOMBE.COM

(213) 674-7238

527 W 7TH STREET
LOS ANGELES, CA 90014
(213) 627-6687

CIVIL ENGINEER:

TALISMA
5217 SOUTH STATE STREET

MURRAY, UT 84107

(801) 743-1300

MECHANICAL / PL

ELECTRICAL:

ABRARI & ASSOCIATES

ABRARI & ASSOCIATES

GLENDALE, CA

(123) 456-7894

BRARI
GINEERING

ARGENTO/GRAHAM

811 WEST 7TH STREET, 10TH FLOOR

LOS ANGELES, CA 90017

WWW.ARGENTOGRAHAM.COM

(323) 536-2578

GEOTECHNICAL:

AM

2702 SOUTH 1030 WEST SUITE 10

SOUTH SALT LAKE, UT 84020

(801) 270-9400

WWW.IGESINC.COM

328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295 328 W 200 S SUITE 102
SALT LAKE CITY, UT 84101
(801) 583-1295

WWW.KGMLIGHTING.COM

TCC PROJECT NUMBER: 18-009



COVER SHEET:

REVISIONS: BY: DATE: DATE: 07/05/2018

SCALE: NA JLB

SHEET:

PATH: N:\SLB0793\Cadd\18-009-Powder Mountain Lot 44R\IP\C000 COVER SHEET.dwg

DATE: 7/5/2018 1:

GENERAL NOTES

- 1. ALL CONSTRUCTION MUST STRICTLY FOLLOW THE STANDARDS AND SPECIFICATIONS SET FORTH BY: GOVERNING UTILITY MUNICIPALITY, GOVERNING CITY OR COUNTY (IF UN-INCORPORATED), INDIVIDUAL PRODUCT MANUFACTURERS, THE DESIGN ENGINEER, AND AMERICAN PUBLIC WORKS ASSOCIATION (APWA). THE ORDER LISTED ABOVE IS ARRANGED BY SENIORITY. IF A CONSTRUCTION PRACTICE IS NOT SPECIFIED BY ANY OF THE LISTED SOURCES, CONTRACTOR MUST CONTACT DESIGN ENGINEER FOR
- 2. CONTRACTOR TO STRICTLY FOLLOW GEOTECHNICAL RECOMMENDATIONS FOR THIS PROJECT. ALL GRADING INCLUDING BUT NOT LIMITED TO CUT, FILL, COMPACTION, ASPHALT SECTION. SUBBASE. TRENCH EXCAVATION/BACKFILL. SITE GRUBBING. RETAINING WALLS AND FOOTINGS MUST BE COORDINATED DIRECTLY WITH THE PROJECT GEOTECHNICAL ENGINEER.
- 3. TRAFFIC CONTROL, STRIPING & SIGNAGE TO CONFORM TO CURRENT UDOT TRANSPORTATION ENGINEER'S MANUAL AND MANUAL OF UNIFORM TRAFFIC CONTROL
- 4. ANY AREA OUTSIDE THE LIMIT OF WORK THAT IS DISTURBED SHALL BE RESTORED TO ITS ORIGINAL CONDITION AT NO COST TO OWNER.
- 5. CONSULT ALL OF THE DRAWINGS AND SPECIFICATIONS FOR COORDINATION
- REQUIREMENTS BEFORE COMMENCING CONSTRUCTION. 6. AT ALL LOCATIONS WHERE EXISTING PAVEMENT ABUTS NEW CONSTRUCTION, THE EDGE
- OF THE EXISTING PAVEMENT SHALL BE SAWCUT TO A CLEAN, SMOOTH EDGE. 7. ALL CONSTRUCTION AND MATERIALS SHALL BE IN ACCORDANCE WITH THE MOST
- RECENT, ADOPTED EDITION OF ADA ACCESSIBILITY GUIDELINES.
- 8. PRIOR TO STARTING CONSTRUCTION, THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAKING SURE THAT ALL REQUIRED PERMITS AND APPROVALS HAVE BEEN OBTAINED. NO CONSTRUCTION OR FABRICATION SHALL BEGIN UNTIL THE CONTRACTOR HAS RECEIVED THOROUGHLY REVIEWED PLANS AND OTHER DOCUMENTS APPROVED BY ALL OF THE PERMITTING AUTHORITIES.
- 9. CONTRACTOR IS RESPONSIBLE FOR SCHEDULING AND NOTIFYING ENGINEER OR INSPECTING AUTHORITY 48 HOURS IN ADVANCE OF COVERING UP ANY PHASE OF CONSTRUCTION REQUIRING OBSERVATION.
- 10. ANY WORK IN THE PUBLIC RIGHT-OF-WAY WILL REQUIRE PERMITS FROM THE APPROPRIATE, CITY, COUNTY OR STATE AGENCY CONTROLLING THE ROAD, INCLUDING OBTAINING REQUIRED INSPECTIONS.
- 11. ALL DIMENSIONS, GRADES & UTILITY DESIGNS SHOWN ON THE PLANS SHALL BE VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION. CONTRACTOR SHALL NOTIFY ENGINEER OF ANY DISCREPANCIES PRIOR TO PROCEEDING WITH CONSTRUCTION FOR NECESSARY PLAN OR GRADE CHANGES.
- 12. CONTRACTOR MUST VERIFY ALL EXISTING CONDITIONS BEFORE BIDDING AND BRING UP ANY QUESTIONS BEFOREHAND.
- 13. SITE GRADING SHALL BE PERFORMED IN ACCORDANCE WITH THESE PLANS AND SPECIFICATIONS AND THE RECOMMENDATIONS SET FORTH BY THE GEOTECHNICAL
- 14. CATCH SLOPES SHALL BE GRADED AS SPECIFIED ON GRADING PLANS.
- 15. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL FLAGGING, CAUTION SIGNS, LIGHTS, BARRICADES, FLAGMEN, AND ALL OTHER DEVICES NECESSARY FOR PUBLIC SAFETY. 16. CONTRACTOR SHALL, AT THE TIME OF BIDDING AND THROUGHOUT THE PERIOD OF THE CONTRACT, BE LICENSED IN THE STATE OF UTAH AND SHALL BE BONDABLE FOR AN
- AMOUNT EQUAL TO OR GREATER THAN THE AMOUNT BID AND TO DO THE TYPE OF WORK CONTEMPLATED IN THE PLANS AND SPECIFICATIONS. CONTRACTOR SHALL BE SKILLED AND REGULARLY ENGAGED IN THE GENERAL CLASS AND TYPE OF WORK CALLED FOR IN THE PLANS AND SPECIFICATIONS. 17. CONTRACTOR SHALL INSPECT THE SITE OF THE WORK PRIOR TO BIDDING TO SATISFY HIMSELF BY PERSONAL EXAMINATION OR BY SUCH OTHER MEANS AS HE MAY PREFER OF THE LOCATION OF THE PROPOSED WORK AND OF THE ACTUAL CONDITIONS OF
- AND AT THE SITE OF WORK. IF, DURING THE COURSE OF HIS EXAMINATION, A BIDDER FINDS FACTS OR CONDITIONS WHICH APPEAR TO HIM TO BE IN CONFLICT WITH THE LETTER OR SPIRIT OF THE PROJECT PLANS AND SPECIFICATIONS, HE SHALL CONTACT THE ENGINEER FOR ADDITIONAL INFORMATION AND EXPLANATION BEFORE SUBMITTING HIS BID. SUBMISSION OF A BID BY THE CONTRACTOR SHALL CONSTITUTE ACKNOWLEDGMENT THAT, IF AWARDED THE CONTRACT, HE HAS RELIED AND IS RELYING ON HIS OWN EXAMINATION OF (1) THE SITE OF THE WORK, (2) ACCESS TO THE SITE. AND (3) ALL OTHER DATA AND MATTERS REQUISITE TO THE FULFILLMENT OF THE WORK AND ON HIS OWN KNOWLEDGE OF EXISTING FACILITIES ON AND IN THE VICINITY OF THE SITE OF THE WORK TO BE CONSTRUCTED UNDER THIS CONTRACT. THE INFORMATION PROVIDED BY THE ENGINEER IS NOT INTENDED TO BE A SUBSTITUTE FOR, OR A SUPPLEMENT TO, THE INDEPENDENT VERIFICATION BY THE CONTRACTOR TO THE EXTENT SUCH INDEPENDENT INVESTIGATION OF SITE CONDITIONS IS DEEMED NECESSARY OR DESIRABLE BY THE CONTRACTOR. CONTRACTOR SHALL ACKNOWLEDGE THAT HE HAS NOT RELIED SOLELY UPON OWNER- OR ENGINEER-FURNISHED INFORMATION REGARDING SITE CONDITIONS IN PREPARING AND
- 18. CONTRACTOR SHALL BE RESPONSIBLE TO PROVIDE ALL WATER, POWER, SANITARY FACILITIES AND TELEPHONE SERVICES AS REQUIRED FOR THE CONTRACTOR'S USE DURING CONSTRUCTION.
- 19. CONTRACTOR SHALL BE HELD RESPONSIBLE FOR ANY FIELD CHANGES MADE WITHOUT PRIOR WRITTEN AUTHORIZATION FROM THE OWNER, ENGINEER, AND/OR GOVERNING
- 20. CONTRACTOR SHALL EXERCISE DUE CAUTION AND SHALL CAREFULLY PRESERVE BENCH MARKS, CONTROL POINTS, REFERENCE POINTS AND ALL SURVEY STAKES, AND SHALL BEAR ALL EXPENSES FOR REPLACEMENT AND/OR ERRORS CAUSED BY THEIR UNNECESSARY LOSS OR DISTURBANCE.
- 21. CONTRACTOR SHALL ASSUME SOLE AND COMPLETE RESPONSIBILITY FOR JOBSITE CONDITIONS DURING THE COURSE OF CONSTRUCTION OF THIS PROJECT, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY. THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS. THE CONTRACTOR SHALL DEFEND, INDEMNIFY AND HOLD THE OWNER AND ENGINEER HARMLESS FROM ANY AND ALL LIABILITY, REAL OR ALLEGED, IN CONNECTION WITH THE PERFORMANCE OF WORK ON THIS PROJECT, EXCEPTING FOR LIABILITY ARISING FROM THE SOLE NEGLIGENCE OF THE OWNER OR THE ENGINEER.
- 22. CONTRACTOR SHALL BE RESPONSIBLE FOR ADEQUATELY SCHEDULING INSPECTION AND TESTING OF ALL FACILITIES CONSTRUCTED UNDER THIS CONTRACT. ALL TESTING SHALL CONFORM TO THE REGULATORY AGENCY'S STANDARD SPECIFICATIONS. ALL TESTING AND INSPECTION SHALL BE PAID FOR BY THE CONTRACTOR.

GENERAL NOTES CONT.

- 23. IF EXISTING IMPROVEMENTS NEED TO BE DISTURBED AND/OR REMOVED FOR THE PROPER PLACEMENT OF IMPROVEMENTS TO BE CONSTRUCTED BY THESE PLANS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING EXISTING IMPROVEMENTS FROM DAMAGE. COST OF REPLACING OR REPAIRING EXISTING IMPROVEMENTS SHALL BE INCLUDED IN THE UNIT PRICE BID FOR ITEMS REQUIRING REMOVAL AND/OR REPLACEMENT. THERE WILL BE NO EXTRA COST DUE TO THE CONTRACTOR FOR REPLACING OR REPAIRING EXISTING IMPROVEMENTS.
- 24. WHENEVER EXISTING FACILITIES ARE REMOVED, DAMAGED, BROKEN, OR CUT IN THE INSTALLATION OF THE WORK COVERED BY THESE PLANS OR SPECIFICATIONS, SAID FACILITIES SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE WITH MATERIALS EQUAL TO OR BETTER THAN THE MATERIALS USED IN THE ORIGINAL EXISTING FACILITIES. THE FINISHED PRODUCT SHALL BE SUBJECT TO THE APPROVAL OF THE OWNER, THE ENGINEER, AND THE RESPECTIVE REGULATORY AGENCY.
- 25. CONTRACTOR SHALL MAINTAIN A NEATLY MARKED SET OF FULL—SIZE AS—BUILT RECORD DRAWINGS SHOWING THE FINAL LOCATION AND LAYOUT OF ALL STRUCTURES AND OTHER FACILITIES. AS-BUILT RECORD DRAWINGS SHALL REFLECT CHANGE ORDERS, ACCOMMODATIONS, AND ADJUSTMENTS TO ALL IMPROVEMENTS CONSTRUCTED. WHERE NECESSARY, SUPPLEMENTAL DRAWINGS SHALL BE PREPARED AND SUBMITTED BY THE CONTRACTOR. PRIOR TO ACCEPTANCE OF THE PROJECT, THE CONTRACTOR SHALL DELIVER TO THE ENGINEER ONE SET OF NEATLY MARKED AS-BUILT RECORD DRAWINGS SHOWING THE INFORMATION REQUIRED ABOVE. AS-BUILT RECORD DRAWINGS SHALL BE REVIEWED AND THE COMPLETE AS-BUILT RECORD DRAWING SET SHALL BE CURRENT WITH ALL CHANGES AND DEVIATIONS REDLINED AS A PRECONDITION TO THE FINAL PROGRESS PAYMENT APPROVAL AND OR FINAL ACCEPTANCE.
- 26. WHERE THE PLANS OR SPECIFICATIONS DESCRIBE PORTIONS OF THE WORK IN GENERAL TERMS BUT NOT IN COMPLETE DETAIL, IT IS UNDERSTOOD THAT ONLY THE BEST GENERAL PRACTICE IS TO PREVAIL AND THAT ONLY MATERIALS AND WORKMANSHIP OF THE FIRST QUALITY ARE TO BE USED.
- 27. CONTRACTOR SHALL BE SKILLED AND REGULARLY ENGAGED IN THE GENERAL CLASS AND TYPE OF WORK CALLED FOR IN THE PROJECT PLANS AND SPECIFICATIONS. THEREFORE, THE OWNER IS RELYING UPON THE EXPERIENCE AND EXPERTISE OF THE CONTRACTOR. PRICES PROVIDED WITHIN THE CONTRACT DOCUMENTS SHALL INCLUDE ALL LABOR AND MATERIALS NECESSARY AND PROPER FOR THE WORK CONTEMPLATED AND THAT THE WORK BE COMPLETED IN ACCORDANCE WITH THE TRUE INTENT AND PURPOSE OF THESE PLANS AND SPECIFICATIONS. THE CONTRACTOR SHALL BE COMPETENT, KNOWLEDGEABLE AND HAVE SPECIAL SKILLS IN THE NATURE, EXTENT AND INHERENT CONDITIONS OF THE WORK TO BE PERFORMED. CONTRACTOR SHALL ALSO ACKNOWLEDGE THAT THERE ARE CERTAIN PECULIAR AND INHERENT CONDITIONS EXISTENT IN THE CONSTRUCTION OF THE PARTICULAR FACILITIES WHICH MAY CREATE, DURING THE CONSTRUCTION PROGRAM, UNUSUAL OR UNSAFE CONDITIONS HAZARDOUS TO PERSONS, PROPERTY AND THE ENVIRONMENT. CONTRACTOR SHALL BE AWARE OF SUCH PECULIAR RISKS AND HAVE THE SKILL AND EXPERIENCE TO FORESEE AND TO ADOPT PROTECTIVE MEASURES TO ADEQUATELY AND SAFELY PERFORM THE CONSTRUCTION WORK WITH RESPECT TO SUCH HAZARDS.
- 28. CONTRACTOR SHALL PROVIDE ALL SHORING, BRACING, SLOPING OR OTHER PROVISIONS NECESSARY TO PROTECT WORKMEN FOR ALL AREAS TO BE EXCAVATED TO A DEPTH OF 4' OR MORE. FOR EXCAVATIONS 4 FEET OR MORE IN DEPTH, THE CONTRACTOR SHALL COMPLY WITH INDUSTRIAL COMMISSION OF UTAH SAFETY ORDERS SECTION 68 - EXCAVATIONS, AND SECTION 69 -TRENCHES, ALONG WITH ANY LOCAL CODES OR ORDINANCES.

UTILITY NOTES

- 1. CONTRACTOR SHALL COORDINATE LOCATION OF NEW "DRY UTILITIES" WITH THE APPROPRIATE UTILITY COMPANY, INCLUDING BUT NOT LIMITED TO: TELEPHONE SERVICE, GAS SERVICE, CABLE, POWER, INTERNET.
- 2. EXISTING UTILITIES HAVE BEEN SHOWN ON THE PLANS USING A COMBINATION OF ON-SITE SURVEYS (BY OTHERS). PRIOR TO COMMENCING ANY WORK, IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO HAVE EACH UTILITY COMPANY LOCATE, IN THE FIELD, THEIR MAIN AND SERVICE LINES. THE CONTRACTOR SHALL NOTIFY BLUE STAKES AT 1-800-662-4111 48 HOURS IN ADVANCE OF PERFORMING ANY EXCAVATION WORK. THE CONTRACTOR SHALL RECORD THE BLUE STAKES ORDER NUMBER AND FURNISH ORDER NUMBER TO OWNER AND ENGINEER PRIOR TO ANY EXCAVATION. IT WILL BE THE CONTRACTOR'S SOLE RESPONSIBILITY TO DIRECTLY CONTACT ANY OTHER UTILITY COMPANIES THAT ARE NOT MEMBERS OF BLUE STAKES. IT SHALL BE THE CONTRACTOR'S SOLE RESPONSIBILITY TO PROTECT ALL EXISTING UTILITIES SO THAT NO DAMAGE RESULTS TO THEM DURING THE PERFORMANCE OF THIS CONTRACT. ANY REPAIRS NECESSARY TO DAMAGED UTILITIES SHALL BE PAID FOR BY THE CONTRACTOR. THE CONTRACTOR SHALL BE REQUIRED TO COOPERATE WITH OTHER CONTRACTORS AND UTILITY COMPANIES INSTALLING NEW STRUCTURES, UTILITIES AND SERVICE TO THE PROJECT.
- 3. CONTRACTOR SHALL POT HOLE ALL UTILITIES TO DETERMINE IF CONFLICTS EXIST PRIOR TO BEGINNING ANY EXCAVATION. NOTIFY ENGINEER OF ANY CONFLICTS. CONTRACTOR SHALL VERIFY LOCATION AND INVERTS OF EXISTING UTILITIES TO WHICH NEW UTILITIES WILL BE CONNECTED. PRIOR TO COMMENCING ANY EXCAVATION WORK THE CONTRACTOR SHALL NOTIFY ALL UTILITY COMPANIES IN ACCORDANCE WITH THE REQUIRED PROCEDURES.
- 4. CARE SHOULD BE TAKEN IN ALL EXCAVATIONS DUE TO POSSIBLE EXISTENCE OF UNRECORDED UTILITY LINES. EXCAVATION REQUIRED WITHIN PROXIMITY OF EXISTING UTILITY LINES SHALL BE DONE BY HAND. CONTRACTOR SHALL REPAIR ANY DAMAGE TO EXISTING UTILITY LINES OR STRUCTURES INCURRED DURING CONSTRUCTION OPERATIONS AT HIS EXPENSE.
- 5. ALL VALVES AND MANHOLE COVERS SHALL BE RAISED OR LOWERED TO MEET FINISHED GRADE.
- 6. CONTRACTOR SHALL CUT PIPES OFF FLUSH WITH THE INSIDE WALL OF THE BOX OR MANHOLE.
- 7. CONTRACTOR SHALL GROUT AT CONNECTION OF PIPE TO BOX WITH NON-SHRINKING GROUT, INCLUDING PIPE VOIDS LEFT BY CUTTING PROCESS, TO A
- SMOOTH FINISH. 8. CONTRACTOR SHALL GROUT WITH NON-SHRINK GROUT BETWEEN GRADE RINGS, BOTTOM OF INLET, LID FRAME, AND TOP OF CONCRETE BOX.
- 9. SILT AND DEBRIS IS TO BE CLEANED OUT OF ALL STORM DRAIN BOXES. CATCH BASINS ARE TO BE MAINTAINED IN A CLEANED CONDITION AS NEEDED UNTIL
- AFTER THE FINAL BOND RELEASE INSPECTION. 10. CONTRACTOR SHALL CLEAN ASPHALT, TAR OR OTHER ADHESIVES OFF OF ALL MANHOLE LIDS AND INLET GRATES TO ALLOW ACCESS.
- 11. EACH TRENCH SHALL BE EXCAVATED SO THAT THE PIPE CAN BE LAID TO THE ALIGNMENT AND GRADE AS REQUIRED. THE TRENCH WALL SHALL BE SO BRACED THAT THE WORKMEN MAY WORK SAFELY AND EFFICIENTLY. ALL TRENCHES SHALL BE DRAINED SO THE PIPE LAYING MAY TAKE PLACE IN DEWATERED CONDITIONS. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR THE COST OF DEWATERING AND NO COST CHANGE WILL BE PROVIDED.
- 12. CONTRACTOR SHALL PROVIDE AND MAINTAIN AT ALL TIMES AMPLE MEANS AND DEVICES WITH WHICH TO REMOVE PROMPTLY AND TO PROPERLY DISPOSE OF ALL WATER ENTERING THE TRENCH EXCAVATION.
- 13. MAINTAIN A MINIMUM 18" VERTICAL SEPARATION DISTANCE BETWEEN ALL UTILITY CROSSINGS.
- 14. CONTRACTOR SHALL START INSTALLATION AT LOW POINT OF ALL NEW GRAVITY UTILITY LINES.
- 15. ALL BOLTED FITTINGS MUST BE GREASED AND WRAPPED
- 16. UNLESS SPECIFICALLY NOTED OTHERWISE, MAINTAIN AT LEAST 2 FEET OF COVER
- OVER ALL STORM DRAIN LINES AT ALL TIMES (INCLUDING DURING CONSTRUCTION). 17. ALL WATER LINES SHALL BE INSTALLED A MINIMUM OF 60" OF COVER TO TOP OF PIPE BELOW FINISHED GRADE.
- 18. ALL SEWER LINES AND SEWER SERVICES SHALL HAVE A MINIMUM SEPARATION OF 10 FEET, PIPE EDGE TO PIPE EDGE, FROM THE WATER LINES.
- 19. CONTRACTOR SHALL INSTALL THRUST BLOCKING AT ALL WATERLINE ANGLE POINTS
- 20. ALL UNDERGROUND UTILITIES SHALL BE IN PLACE PRIOR TO INSTALLATION OF CURB. GUTTER. SIDEWALK AND STREET PAVING.
- 21. CONTRACTOR SHALL INSTALL MAGNETIC LOCATING TAPE CONTINUOUSLY OVER ALL NONMETALLIC PIPE.
- 22. THE CONTRACTOR SHALL NOTIFY TALISMAN CIVIL CONSULTANTS, LLC. IN WRITING AT LEAST 48 HOURS PRIOR TO BACKFILLING OF ANY PIPE WHICH STUBS TO A FUTURE PHASE OF CONSTRUCTION FOR INVERT VERIFICATION. TOLERANCE SHALL BE IN ACCORDANCE WITH THE REGULATORY AGENCY STANDARD SPECIFICATIONS.
- 23. UNDER NO CIRCUMSTANCE SHALL THE PIPE OR ACCESSORIES BE DROPPED INTO THE TRENCH

WEBER COUNTY

2380 WASHINGTON BLVD. #240 OGDEN, UT 84401 (801) 399-8374

ROCKY MOUNTIAN POWER

1438 WEST 2550 SOUTH OGDEN, UT 84401 (801) 629-4429

POWDER MOUNTAIN WATER & SEWER DISTRICT

PO BOX 270 EDEN, UT 84310 (801) 745-0912

LEGEND:

SYMBOL / LINETYPE DESCRIPTION EXISTING WATER PIPE EXISTING WATER VALVE EXISTING SANITARY SEWER PIPE EXISTING SANITARY SEWER MANHOLE EXISTING TELECOMMUNICATION CONDUIT _____СПМ ____ EXISTING TELECOMMUNICATION PULL BOX EXISTING ELECTRICAL CONDUIT EXISTING ELECTRICAL PULL BOX EXISTING ELECTRICAL TRANSFORMER EXISTING STORM DRAIN LINE -----4"SD-----PROPOSED CONCRETE PROPOSED WATER VALVE PROPOSED WATER METER PROPOSED WATER PIPE PROPOSED SANITARY SEWER GRINDER PUMP PROPOSED 1 1/2"ø PRESSURE SEWER PIPE ——1½′′SS−P ——— PROPOSED GAS PIPE PROPOSED ELECTRICAL CONDUIT PROPOSED 4" ADS PERFORATED STORM DRAIN PIPE -----4"SD------PROPOSED TELECOMMUNICATIONS CONDUIT

NOTE: LEGEND MAY CONTAIN SYMBOLS THAT ARE NOT USED IN PLAN SET.

EROSION CONTROL GENERAL NOTES.

THE CONTRACTOR TO USE BEST MANAGEMENT PRACTICES FOR PROVIDING EROSION CONTROL FOR CONSTRUCTION OF THIS PROJECT. ALL MATERIAL AND WORKMANSHIP SHALL CONFORM TO WEBER COUNTY ORDINANCES AND ALL WORK SHALL BE SUBJECT TO INSPECTION BY THE COUNTIES. ALSO, INSPECTORS WILL HAVE THE RIGHT TO CHANGE THE FACILITIES AS NEEDED.

CONTRACTOR SHALL KEEP THE SITE WATERED TO CONTROL DUST. CONTRACTOR TO LOCATE A NEARBY HYDRANT FOR USE AND TO INSTALL TEMPORARY METER. CONSTRUCTION WATER COST TO BE INCLUDED IN BID.

WHEN GRADING OPERATIONS ARE COMPLETED AND THE DISTURBED GROUND IS LEFT "OPEN" FOR 14 DAYS OR MORE, THE AREA SHALL BE FURROWED PARALLEL TO THE CONTOURS.

THE CONTRACTOR SHALL MODIFY EROSION CONTROL MEASURES TO ACCOMMODATE PROJECT PLANNING.

ALL ACCESS TO PROPERTY WILL BE FROM PUBLIC RIGHT-OF-WAYS.

THE CONTRACTOR IS REQUIRED BY STATE AND FEDERAL REGULATIONS TO PREPARE A STORM WATER POLLUTION PREVENTION PLAN AND FILE A "NOTICE OF INTENT" WITH THE UTAH DIVISION OF WATER QUALITY.

ALL BEST MANAGEMENT PRACTICES (BMP'S) SHOWN ON THIS PLAN MUST BE MAINTAINED AT ALL TIMES UNTIL VEGETATION IS RE-ESTABLISHED.

THE CONTRACTOR'S RESPONSIBILITY SHALL INCLUDE MAKING BI-WEEKLY CHECKS ON ALL EROSION CONTROL MEASURES TO DETERMINE IF REPAIR OR SEDIMENT REMOVAL IS NECESSARY. CHECKS SHALL BE DOCUMENTED AND COPIES OF THE INSPECTIONS KEPT ON SITE.

SEDIMENT DEPOSITS SHOULD BE REMOVED AFTER EACH RAINFALL. THEY MUST BE REMOVED WHEN THE LEVEL OF DEPOSITION REACHES APPROXIMATELY ONE-HALF THE HEIGHT OF BARRIER.

SEDIMENT TRACKED ONTO PAVED ROADS MUST BE CLEANED UP AS SOON AS PRACTICAL. BUT IN NO CASE LATER THAN THE END OF THE NORMAL WORK DAY. THE CLEAN UP WILL INCLUDE SWEEPING OF THE TRACKED MATERIAL. PICKING IT UP. AND DEPOSITING IT TO A CONTAINED AREA.

EXPOSED SLOPES:

ANY EXPOSED SLOPE THAT WILL REMAIN UNTOUCHED FOR LONGER THAN 14 DAYS MUST BE STABILIZED BY ONE OR MORE OF THE FOLLOWING METHODS:

- A) SPRAYING DISTURBED AREAS WITH A TACKIFIER VIA HYDROSEED B) TRACKING STRAW PERPENDICULAR TO SLOPES
- C) INSTALLING A LIGHT—WEIGHT, TEMPORARY EROSION CONTROL BLANKET

ABBREVIATIONS:

BG - BUILDING

BS - BOTTOM OF STAIRS BW - BOTTOM OF WALL

EX - EXISTING


FL - FLOWLINE

FG - FINISHED GROUND MA - MATCH

TS - TOP OF STAIRS

TW - TOP OF WALL

RIM - RIM OF MANHOLE R COMPLIANCE WITH THE APPLICA X STRUCTURAL MECHANICAL PLUMBING X ELECTRICAL X ENERGY TACCESSIBILITY ☐ FIRE STATE, OR LOCAL REGULATIONS. MEM



PATH: N:\SLB0793\Cadd\18-009-Powder Mountain Lot 44R\IP\C001 GENERAL NOTES AND LEGEND.dwg

POWDER MOUNTAIN HOUSE TOM BUTTGENBACH 8645 EASET COPPER CREST FIRM IIT 84310

MECHANICAL / PLUMBING:

LANDSCAPE ARCHITECT:

LIGHTING DESIGNER: LDG 328 W 200 S SUITE 102

KGM SALT LAKE CITY, UT 84101

WWW.KGMLIGHTING.COM

(801) 583-1295



GENERAL NOTES REVISIONS: BY: DATE: DATE: 07/05/2018 SCALE: DRAWN: NA SHEET:

DATE: 07/11/1

ST COAST CODE CONSULTANTS. II

TOM WISCOMBE **ARCHITECTURE** 2404 WILSHIRE BLVD., SUITE 4B

OS ANGELES, CA 90057

WWW.TOMWISCOMBE.CO

(213) 674-7238

527 W 7TH STREET OS ANGELES, CA 90014 213) 627-6687 WWW.NOUSENGINEERING.COM

STRUCTURAL ENGINEER:

CIVIL ENGINEER: 5217 SOUTH STATE STREET

MURRAY, UT 84107

(801) 743-1300

TALISMAN SHAMIM 5530 CORBIN AVE. SUITE 300 TARZANA, CA 91356 (818) 788-6778 WWW.TALISMANCIVIL.COM

WWW.SHAMIMENGINEERING.COM

GLENDALE, CA (123) 456-7894 WWW.ABRARI.COM

B11 WEST 7TH STREET, 10TH FLOOR LOS ANGELES, CA 90017 (323) 536-2578 WWW.ARGENTOGRAHAM.COM

NGBS CONSULTING:


ARGENTO/GRAHAM


2702 SOUTH 1030 WEST SUITE 10 SOUTH SALT LAKE, UT 84020 (801) 270-9400 WWW.IGESINC.COM


328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295

TCC PROJECT NUMBER: 18-009

DATE: 7/5/2018 1:35 PM







(213) 674-7238

(213) 627-6687

811 WEST 7TH STREET, 10TH FLOOR LOS ANGELES, CA 90017

(323) 536-2578 WWW.ARGENTOGRAHAM.COM

TALISMAN ENGINEERING CONSULTANTS INC. ABRARI ENGINEERING

GLENDALE, CA

(123) 456-7894

TARZANA, CA 91356

(818) 788-6778

5217 SOUTH STATE STREET MURRAY, UT 84107


(801) 743-1300

328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295 2702 SOUTH 1030 WEST SUITE 10 SOUTH SALT LAKE, UT 84020 (801) 270-9400


KGM 328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295 WWW.KGMLIGHTING.COM



TCC PROJECT NUMBER: 18-009



07/05/2018 C300



PATH: N:\SLB0793\Cadd\18-009-Powder Mountain Lot 44R\IP\C301 CUT FILL ANALYSIS.dwg

DATE: 7/5/2018 1: 37

<u>UTILITIES:</u>
ENSURE MINIMUM BURIED DEPTH PER BUILDING CODE FOR ALL BURIED UTILITIES.


IMPROVEMENTS, INCLUDING LANDSCAPING, SHALL NOT INTERFERE WITH ANY DRAINAGE CULVERT, RIP RAP, AND DRAINAGE PATTERN ASSOCIATED WITH ANY DRAINAGE EASEMENT.


KEY NOTES:

- 1 Install 4"ø sewer lateral with cleanout per apwa plan no. 431.
- $\langle 2 \rangle$ INSTALL 1 1/2"ø DR-11 IPS PRESSURE SEWER PIPE, MINIMUM COVER OF 72".
- INSTALL E/ONE GRINDER PUMP STATION MODEL DH071. WITH E/ONE SENTRY ALARM PANEL INCLUDING GENERATOR RECEPTACLE WITH AUTO TRANSFER AND GFCI RECEPTACLE.

 ALARM PANELS SHALL BE INSTALLED WITHIN LINE OF SIGHT OF ENTRY TO UNIT. SEE DETAIL SHEET A/703.
- 4 CONNECT TO EXISTING SANITARY SEWER LATERAL PER DETAIL B/SHEET 703.
- $\langle 5 \rangle$ INSTALL CULINARY WATER AND FIRE LINES PER DETAIL A/SHEET 702.
- 6 INSTALL ELECTRICAL LINE FROM SERVICE BOX TO BUILDING.
- $\overline{\langle 7 \rangle}$ INSTALL TELECOMMUNICATIONS LINE FROM SERVICE BOX TO BUILDING.
- (8) INSTALL PROPANE TANKS PER DETAIL B/SHEET 702. SERVICE LINE TO BUILDING TO BE INSTALLED BY OTHERS.
- 9 SEE MECHANICAL PLANS FOR CONTINUATION OF UTILITY WITHIN BUILDING.
- EXISTING SLOPE DRAIN PIPE. DEMO AS NECESSARY FOR CONSTRUCTION. REPAIR AND TIE INTO NEW FOUNDATION DRAIN. SEE STRUCTURAL PLANS FOR FOUNDATION DRAIN DETAILS.
- (11) EXISTING SEWER LATERAL.
- (12) EXISTING WATER LATERAL.
- (13) PROTECT EXISTING 8" WATER PIPE IN PLACE.
- (14) EXISTING WATER EASEMENT.
- INSTALL 4"Ø ADS PIPE, CONNECT TO DOWNSPOUT (GUTTER DRAIN LEADER) PER DETAIL

 (15) D/SHEET 702. MAINTAIN 24" OF COVER OVER PIPE. TIE INTO TRENCH DRAIN 4"Ø
- INSTALL 4"Ø ADS PERFORATED PIPE WITHIN GRAVEL TRENCH, SEE DETAIL E/SHEET C702.
 MAINTAIN POSITIVE DRAINAGE TO OUTLET.
- INSTALL 4"Ø ADS OUTLET PIPE. DAYLIGHT OUTLET TO FINISHED SLOPE, SECURELY FASTEN 17) 17 WIRE MESH TO OUTLET TO PROTECT WILDLIFE AND DEBRIS FROM ENTERING PIPE





POWDER MOUNTAIN HOUSE TOM BUTTGENBACH 8645 EASET COPPER CREST EDEN, UT 84310


KGM 328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101

(801) 583-1295

WWW.KGMLIGHTING.COM



TCC PROJECT NUMBER: 18-009



UTILITY PLAN 07/05/2018 C400

TOM WISCOMBE

LOS ANGELES, CA 90057

WWW.TOMWISCOMBE.COM

(213) 674-7238

LOS ANGELES, CA 90014 (213) 627-6687

TALISMAN SILIANTS SHAMIM ABRARI ENGINEERING

MURRAY, UT 84107

WWW.TALISMANCIVIL.COM

(801) 743-1300

TARZANA, CA 91356

5530 CORBIN AVE. SUITE 300 (818) 788-6778 WWW.SHAMIMENGINEERING.COM

GLENDALE, CA (123) 456-7894

811 WEST 7TH STREET, 10TH FLOOR LOS ANGELES, CA 90017 (323) 536-2578 WWW.ARGENTOGRAHAM.COM


ARGENTO/GRAHAM

2702 SOUTH 1030 WEST SUITE 10 SOUTH SALT LAKE, UT 84020 (801) 270-9400 WWW.IGESINC.COM

DATE: 7/5/2018 1:28 PM

(801) 583-1295

SALT LAKE CITY, UT 84101



EROSION CONTROL GENERAL NOTES:

THE CONTRACTOR TO USE BEST MANAGEMENT PRACTICES FOR PROVIDING EROSION CONTROL FOR CONSTRUCTION OF THIS PROJECT. ALL MATERIAL AND WORKMANSHIP SHALL CONFORM TO WEBER COUNTY ORDINANCES AND ALL WORK SHALL BE SUBJECT TO INSPECTION BY THE COUNTY. ALSO, INSPECTORS WILL HAVE THE RIGHT TO CHANGE THE FACILITIES AS NEEDED.

CONTRACTOR SHALL KEEP THE SITE WATERED TO CONTROL DUST. CONTRACTOR TO LOCATE A NEARBY HYDRANT FOR USE AND TO INSTALL TEMPORARY METER. CONSTRUCTION WATER COST TO BE INCLUDED IN BID.

WHEN GRADING OPERATIONS ARE COMPLETED AND THE DISTURBED GROUND IS LEFT "OPEN" FOR 14 DAYS OR MORE, THE AREA SHALL BE FURROWED PARALLEL

THE CONTRACTOR SHALL MODIFY EROSION CONTROL MEASURES TO ACCOMMODATE PROJECT PLANNING.

ALL ACCESS TO PROPERTY WILL BE FROM PUBLIC RIGHT-OF-WAYS.

THE CONTRACTOR IS REQUIRED BY STATE AND FEDERAL REGULATIONS TO PREPARE A STORM WATER POLLUTION PREVENTION PLAN AND FILE A "NOTICE OF INTENT" WITH THE UTAH DIVISION OF WATER QUALITY.

ALL BEST MANAGEMENT PRACTICES (BMP'S) SHOWN ON THIS PLAN MUST BE MAINTAINED AT ALL TIMES UNTIL VEGETATION IS RE-ESTABLISHED.

THE CONTRACTOR'S RESPONSIBILITY SHALL INCLUDE MAKING BI-WEEKLY CHECKS ON ALL EROSION CONTROL MEASURES TO DETERMINE IF REPAIR OR SEDIMENT REMOVAL IS NECESSARY. CHECKS SHALL BE DOCUMENTED AND COPIES OF THE INSPECTIONS KEPT ON SITE.


SEDIMENT DEPOSITS SHOULD BE REMOVED AFTER EACH RAINFALL. THEY MUST BE REMOVED WHEN THE LEVEL OF DEPOSITION REACHES APPROXIMATELY ONE-HALF THE HEIGHT OF BARRIER.

SEDIMENT TRACKED ONTO PAVED ROADS MUST BE CLEANED UP AS SOON AS PRACTICAL, BUT IN NO CASE LATER THAN THE END OF THE NORMAL WORK DAY. THE CLEAN UP WILL INCLUDE SWEEPING OF THE TRACKED MATERIAL, PICKING IT UP, AND DEPOSITING IT TO A CONTAINED AREA.


ANY EXPOSED SLOPE THAT WILL REMAIN UNTOUCHED FOR LONGER THAN 14 DAYS MUST BE STABILIZED BY ONE OR MORE OF THE FOLLOWING METHODS:

- A) SPRAYING DISTURBED AREAS WITH A TACKIFIER VIA HYDROSEED
- B) TRACKING STRAW PERPENDICULAR TO SLOPES C) INSTALLING A LIGHT-WEIGHT, TEMPORARY EROSION CONTROL BLANKET


PROVIDE, INSTALL AND/OR CONSTRUCT THE FOLLOWING PER THE SPECIFICATIONS GIVEN OR REFERENCED, THE DETAILS NOTED, AND/OR AS SHOWN ON THE CONSTRUCTION DRAWINGS:



HATCHING INDICATES AREAS TO RECEIVE 4" TOPSOIL AND TO BE SEEDED FOR NATURAL VEGETATION. AREAS RECEIVING SEEDING FOR NATURAL REVEGETATION ON SLOPES OF 3:1 OR STEEPER MUST BE COVERED WITH AN EROSION CONTROL BLANKET AFTER THE FINAL GRADING AND SEEDING ARE FINISHED. INSTALL NORTH AMERICAN GREEN SC-150 BLANKET OR APPROVED EQUAL. FOLLOW MANUFACTURER'S SPECIFICATIONS.



STABILIZED CONSTRUCTION ENTRANCE PER APWA PLAN NO. 126.




INSTALL SILT FENCE ALONG DOWN GRADIENT LIMITS OF DISTURBANCE AS SHOWN ON PLAN PER APWA PLAN NO. 122. SEE SHEET 700.

INSTALL ORANGE SAFETY FENCING AROUND OUTER LIMITS OF

SEE LANDSCAPING PLANS FOR SEED MIXTURE

X ELECTRICAL X ENERGY T COAST CODE CONSULTANTS. I



POWDER MOUNTAIN HOUSE TOM BUTTGEN BACH 8645 EASET COPPER CREST EDEN, UT 84310

TOM WISCOMBE

LOS ANGELES, CA 90057

(213) 674-7238

LOS ANGELES, CA 90014 (213) 627-6687

MURRAY, UT 84107

WWW.TALISMANCIVIL.COM

(801) 743-1300

TALISMAN SULTANTS SHAMIM FINE INC.

TARZANA, CA 91356

WWW.SHAMIMENGINEERING.COM

(818) 788-6778

GLENDALE, CA

(123) 456-7894

WWW.ABRARI.COM

ARGENTO/GRAHAM

LOS ANGELES, CA 90017

WWW.ARGENTOGRAHAM.COM

(323) 536-2578

811 WEST 7TH STREET, 10TH FLOOR

SOUTH SALT LAKE, UT 84020

(801) 270-9400

WWW.IGESINC.COM

2702 SOUTH 1030 WEST SUITE 10

SALT LAKE CITY, UT 84101


328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101

(801) 583-1295

WWW.KGMLIGHTING.COM



TCC PROJECT NUMBER: 18-009



EROSION CONTROL REVISIONS: 07/05/2018 1"=20' **C600**

PATH: N:\SLB0793\Cadd\18-009-Powder Mountain Lot 44R\IP\C600 EROSION CONTROL PLAN.dwg

(801) 583-1295

- GENERAL A. Description. A temporary sediment barrier consisting of a filter fabric stretched
- across and attached to supporting posts and entrenched. B. Application. To intercept sediment from disturbed areas of limited extent.
- C. Perimeter Control: Place barrier at down gradient limits of disturbance.
- D. Sediment Barrier: Place barrier at toe of slope or soil stockpile.
- E. Protection of Existing Waterways: Place barrier at top of stream bank.
- F. Inlet Protection.

2. PRODUCTS

- A. Fabric. Synthetic filter fabric shall be a pervious sheet of propylene, nylon. polyester, or polyethylene yarn. Synthetic filter fabric shall contain ultraviolet ray inhibitors and stabilizers to provide a minimum of 6 months of expected usable construction life at a temperature range of 0 deg F to 120 deg F.
- B. Burlap. 10 ounces per square yard of fabric.
- C. Posts. Either 2" x 4" diameter wood, or 1.33 pounds per linear foot steel with a minimum length of 5 feet, or steel posts with projections for fastening wire to them.

3. EXECUTION

- A. Cut the fabric on site to desired width, unroll, and drape over the barrier. Secure the fabric toe with rocks or dirt and secure the fabric to the mesh with twin, staples or
- B. When attaching two silt fences together, place the end post of the second fence inside the end post of the first fence. Rotate both posts at least 180 degrees on a clockwise direction to create a tight seal with the filter fabric. Drive both posts into the ground and bury the flap.
- C. When used to control sediments from a steep slope, place silt fences away from the toe of the slope for increased holding capacity.
- D. Maintenance.
- 1) Inspect immediately after each rainfall and at least daily during prolonged
- 2) Should the fabric on a silt fence or filter barrier decompose or become ineffective before the end of the expected usable life and the barrier still be necessary, replace the fabric promptly.
- 3) Remove sediment deposits after each storm event. They must be removed when deposits reach approximately one-half the height of the barrier.

THIS PLAN MAY BE USED FOR THE CONSTRUCTION OF A STORM WATER BEST MANAGEMENT PRACTICE

SHOULD BE CONTINUOUSLY MONITORED BY THE CONTRACTOR AND ENGINEER. DETAILS SHOWN HERE

(BMP). IT IS NOT INCLUSIVE OF ALL PRACTICES AVAILABLE AND IS ONLY SPECIFIC TO THE

HIGHLIGHT IMPORTANT PARTS OF CONSTRUCTION, AND SHOULD BE MODIFIED AS NEEDED.

INSTALLATION SEQUENCE

TOE DETAIL

CONSTRUCTION OF THIS TYPE. MAINTENANCE OF THIS TYPE OF INSTALLATION IS IMPORTANT AND

4) Re-anchor fence as necessary to prevent shortcutting. 5) Inspect for runoff bypassing ends of barriers or undercutting barriers.

POSTS WITH WIRE

STAPLES 1" LONG OR TIE WIRES OR HOG RINGS

WITH ENGINEER'S APPROVAL, AN EXTRA STRENGTH FILTER

FABRIC CAN BE USED IN LIEU OF WIRE MESH SUPPORT

- D. Maintenance. 1) Prevent tracking or flow of mud into the public right-of-way.
- 2) Periodic top dressing with 2-inch stone may be required, as conditions demand, and repair any structures used to trap sediments.

construction vehicle access to the site.

(Not used)

1. GENERAL

2. PRODUCT

3 EXECUTION

paved roadway

B. Compact subgrade.

remains more than 3 months).

3) Inspect daily for loss of gravel or sediment buildup. 4) Inspect adjacent area for sediment deposit and install additional controls as

THIS PLAN MAY BE USED FOR THE CONSTRUCTION OF A STORM WATER BEST MANAGEMENT

PRACTICE (BMP). IT IS NOT INCLUSIVE OF ALL PRACTICES AVAILABLE AND IS ONLY SPECIFIC TO

HERE HIGHLIGHT IMPORTANT PARTS OF CONSTRUCTION, AND SHOULD BE MODIFIED AS NEEDED.

THE CONSTRUCTION OF THIS TYPE. MAINTENANCE OF THIS TYPE OF INSTALLATION IS IMPORTANT AND SHOULD BE CONTINUOUSLY MONITORED BY THE CONTRACTOR AND ENGINEER. DETAILS SHOWN

Stabilized roadway entrance

A. Description. A temporary stabilized pad of gravel for controlling equipment and

B. Application. At any site where vehicles and equipment enter the public right of way.

A. Clear and grub area and grade to provide maximum slope of 1 percent away from

C. Place filter fabric under stone if desired (recommended for entrance area that

5) Expand stabilized area as required to accommodate activities.

GENERAL

A. The drawing applies to backfilling the trench above the pipe zone.

Trench backfill

2. PRODUCTS

- A. Backfill: Common fill, APWA Section 31 05 13. Maximum particle size 3-inches.
- B. Flowable Fill: Target is 60 psi in 28 days with 90 psi maximum in 28 days, APWA Section 31 05 15. It must flow easily requiring no vibration for consolidation.

3. EXECUTION

- A. Trench Backfill:
 - 1) DO NOT USE sewer rock, pea gravel, or recycled RAP aggregate as trench
 - 2) Maximum lift thickness is 8-inches before compaction. Compaction is 95 percent or greater relative to a standard proctor density, APWA Section 31 23
 - 3) Water jetting is NOT allowed.
- 4) Submission of quality control compaction test result data developed for haunching areas may be requested by ENGINEER at any time. Provide results of tests immediately upon request.
- B. Flowable Fill: When required, place controlled low strength material in the trench, APWA Section 31 05 15. Cure the fill before placing surface restorations.
- C. Surface Restoration:
- 1) Landscaped Surface: Rake to match existing grade. Replace vegetation to match pre-construction conditions. Follow APWA Section 32 92 00 (turf or grass) or APWA Section 32 93 13 (ground cover) requirements.
- 2) Paved Surface: Do not install asphalt or concrete surfacing until trench compaction is acceptable to ENGINEER. Follow APWA Section 33 05 25 (asphalt surfacing), or APWA Section 33 05 25 (concrete surfacing).

A. Install the pipe in the center of the trench or no closer than 6-inches from the wall of the pipe to the wall of the trench.


Pipe zone backfill

GENERAL

- 2. PRODUCTS A. Base Course: Untreated base course, APWA Section 32 11 23. Do not use gravel as a base course without ENGINEER's permission.
- B. Backfill: Common fill, APWA Section 31 05 13. Maximum particle size 2-inches.
- C. Concrete: APWA Section 03 30 04.
- D. Flowable Fill: Target is 60 psi in 28 days with 90 psi maximum in 28 days, APWA Section 31 05 15. It must flow easily requiring no vibration for consolidation.
- E. Stabilization-Separation Geotextile: Moderate or high at CONTRACTOR's choice, APWA Section 31 05 19.


3. EXECUTION

- A. Excavate the Pipe Zone: Width is measured at the pipe spring line and includes any necessary sheathing. Provide width recommended by pipe manufacturer. Follow manufacturer's recommendations when using trench boxes.
- B. Foundation Stabilization: Get ENGINEER's permission before installing common fill. Vibrate to stabilize. Installation of stabilization-separation geotextile will be required to separate backfill material and native subgrade materials if common fill cannot provide a working surface or prevent soils migration.
- C. Base Course:
- 1) Furnish untreated base course material unless specified otherwise by pipe
- 2) Maximum lift thickness is 8-inches before compaction. Compaction is 95 percent or greater relative to a modified proctor density, APWA Section 31 23
- 3) When using concrete, provide at least Class 2,000 per APWA Section 03 30 04. D. Pipe Zone: DO NOT USE sewer rock, pea gravel, or recycled RAP aggregate in the
- pipe zone. Water jetting is NOT allowed. 1) Maximum lift thickness is 8-inches before compaction. Compaction is 95
- percent or greater relative to a modified proctor density, APWA Section 31 23 26
- unless pipe manufacturer requires more stringent installation. 2) Submission of quality control compaction test result data developed for the haunch zone may be requested by ENGINEER at any time. CONTRACTOR is to provide results of tests immediately upon request.
- E. Flowable Fill (when required and if allowed by pipe manufacturer):
- 1) Place the controlled low strength material, APWA Section 31 05 15.
- 2) Prevent pipe flotation by installing in lifts and providing pipe restraints as required by pipe manufacturer.
- 3) Reset pipe to line and grade if pipe "floats" out of position.



MAKE BELL HOLES BEFORE

ELEVATION VIEW



SECTION A-A

XMECHANICAL **X**PLUMBING XELECTRICAL XENERGY STATE, OR LOCAL REGULATIONS. MEM

EST COAST CODE CONSULTANTS, IN

INSTALLATION

CONCRETE PIPE: FOLLOW ASTM C 1479 C AND HDPE PIPE: FOLLOW ASTM D 2321 CORRUGATED METAL PIPE: FOLLOW ASTM A 798

VITRIFIED CLAY PIPE: FOLLOW ASTM C 12.

Pipe zone backfill 382

DETAILS

Silt fence

122

AVOID JOINTS

February 2006

Stabilized roadway entrance

2" TO 4" SIZE

COARSE AGGREGATE

126

Trench backfill 203

381

January 2011

205

February 2006

POWDER MOUNTAIN HOUSE TOM BUTTGEN BACH 8645 EASET COPPER CREST FIRM IIT RASAID

TARZANA, CA 91356

WWW.SHAMIMENGINEERING.COM

(818) 788-6778

January 2011

LIGHTING DESIGNER: KGN

STRUCTURAL ENGINEER: TOM WISCOMBE

LOS ANGELES, CA 90057 OS ANGELES, CA 90014 (213) 674-7238 213) 627-6687 WWW.TOMWISCOMBE.COM WWW.NOUSENGINEERING.COM

5217 SOUTH STATE STREET MURRAY, UT 84107

(801) 743-1300

WWW.TALISMANCIVIL.COM

CIVIL ENGINEER: TALISMAN 5530 CORBIN AVE. SUITE 300

GLENDALE, CA

(123) 456-7894

WWW.ABRARI.COM

ARGENTO/GRAHAM B11 WEST 7TH STREET, 10TH FLOOR LOS ANGELES, CA 90017 (323) 536-2578 WWW.ARGENTOGRAHAM.COM

NGBS CONSULTING:

2702 SOUTH 1030 WEST SUITE 10 SOUTH SALT LAKE, UT 84020 (801) 270-9400

WWW.IGESINC.COM

328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295

328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295 WWW.KGMLIGHTING.COM

TCC PROJECT NUMBER: 18-009

BY: DATE: DATE: REVISIONS: 07/05/2018 DRAWN: SCALE: SHEET

Sewer lateral connection

1. GENERAL

- A. Before installation, secure acceptance by ENGINEER for all pipe, fittings, and couplings to be used.
- B. Before backfilling, secure inspection of installation by ENGINEER. Give at least 24 hours notice.
- C. Verify if CONTRACTOR or agency is to install the wye.

2. PRODUCTS

- A. Base Course: Untreated base course, APWA Section 32 11 23. Do not use gravel as a base course without ENGINEER's permission.
- B. Backfill: Common fill, APWA Section 31 05 13. Maximum particle size 2-inches.
- C. Provide agency approved wye or tee with appropriate donut. D. Stainless steel straps required.

3. EXECUTION

- A. Tape wrap pipe as required by soil conditions.
- B. Remove core plug from sewer main. Do not break into sewer main to make
- C. Base Course and Backfill Placement: Maximum lift thickness is 8-inches before compaction. Compaction is 95 percent or greater relative to a standard proctor density, APWA Section 31 23 26.

3/4" and 1" meter

1. GENERAL

A. In street surfaces or other vehicular traffic areas (like driveway approaches), Install the same type of meter box as required for 1 1/2" and 2" service meters. See Plan

B. Before backfilling, secure inspection of installation by ENGINEER.

2. PRODUCTS

- A. Base Course: Untreated base course, APWA Section 32 11 23. Do not use gravel as a base course without ENGINEER's permission.
- B. Backfill: Common fill, APWA Section 31 05 13. Maximum particle size 2-inches.
- C. Castings: Grey iron class 35 minimum per ASTM A 48, coated with asphalt based paint or better.

3. EXECUTION

A. Meter Placement:

- 1) All meters are to be installed in the park strip or within 7 feet of the property line 2) Do not install meters under driveway approaches, sidewalks, or curb and gutter.
- B. Meter Box: Set box so grade of the frame and cover matches the grade of the surrounding surface.
- C. Pipe Outside of Right-of-Way: Coordinate with utility agency or adjacent property owner for type of pipe to be used outside of right-of-way.
- D. Inspection: Before backfilling around meter box, secure inspection of installation by ENGINEER.
- E. Base Course and Backfill Placement: Compaction is 95 percent or greater relative to a modified proctor density, APWA Section 31 23 26. Maximum lift thickness before compaction is 8-inches.

Cover collar for water valve box

1. GENERAL


A. In a pavement surface, fill an annular space around a frame and cover casting with concrete. The concrete will support the casting under traffic loadings.


2. PRODUCTS

- A. Base Course: Untreated base course, APWA Section 32 11 23. Do not use gravel as a base course without ENGINEER's permission.
- B. Concrete: Class 4000, APWA Section 03 30 04.
- C. Concrete Curing Agent: Type ID Class A (clear with fugitive dye), membrane forming compound, APWA Section 03 39 00.

3. EXECUTION

- A. Base Course: Maximum lift thickness is 8-inches before compaction. Compaction is 95 percent or greater relative to a modified proctor density, APWA Section 31 23
- B. Pavement Preparation: Provide a neat vertical and concentric joint between concrete collar and existing asphalt concrete surface. Clean edges of all dirt, oil, and loose debris.





LEGEND			
No.	*	ITEM	DESCRIPTION
\odot		FRAME AND COVER	CAST IRON COVER (grass) DUCTILE IRON COVER (driveway)
В		METER BOX (18" TO 21" DIAMETER) (30" TO 36" DEEP)	CORRUGATED PE, PVC, CMP OR MATERIAL ACCEPTABLE TO AGENCY
(O		3/4" METER YOKE	OPTIONAL BACKFLOW PROTECTION PER AGENCY REQUIREMENTS
(1" METER YOKE	OPTIONAL BACKFLOW PROTECTION PER AGENCY REQUIREMENTS
(II)		COPPER PIPE	TYPE K (SOFT)


3/4" and 1" meter

FURNISHED BY UTILITY AGENCY

CONCRETE TO BE SET 1/2" MIN. TO ASPHALT CONCRETE PAVEMENT LIP ALL AROUND SLIP SLEEVE ---SLIP SLEEVE -(ONLY TOP OF VALVE BOX RISERIS SHOWN) CONCRETE PAVEMENT ASPHALT CONCRETE

Cover collar for water valve box

277



TCC PROJECT NUMBER: 18-009

MECHANICAL PLUMBING XELECTRICAL XENERGY
□ ACCESSIBILITY □ FIRE EST COAST CODE CONSULTANTS, IN

DRAWN:

POWDER MOUNTAIN HOUSE TOM BUTTGEN BACH 8645 EASET COPPER CREST EDEN, UT 84310

431

521

LIGHTING DESIGNER: KGM

328 W 200 S SUITE 102

SALT LAKE CITY, UT 84101

WWW.KGMLIGHTING.COM

(801) 583-1295

August 2010

DETAILS BY: DATE: DATE: REVISIONS: 07/05/2018 SCALE: NTS SHEET:

574

STRUCTURAL ENGINEER:

WWW.NOUSENGINEERING.COM

TOM WISCOMBE LOS ANGELES, CA 90057 (213) 674-7238

WWW.TOMWISCOMBE.COM

January 2011

LOS ANGELES, CA 90014 MURRAY, UT 84107 (801) 743-1300 (213) 627-6687

Sewer lateral connection

219

CIVIL ENGINEER: TALISMAN S SHAMIM FINE SHAMIM FOR THE STATE OF THE STATE 5217 SOUTH STATE STREET

WWW.TALISMANCIVIL.COM

5530 CORBIN AVE. SUITE 300 TARZANA, CA 91356 (818) 788-6778

WWW.SHAMIMENGINEERING.COM

GLENDALE, CA (123) 456-7894 WWW.ABRARI.COM

ARGENTO/GRAHAM 811 WEST 7TH STREET, 10TH FLOOR LOS ANGELES, CA 90017 (323) 536-2578 WWW.ARGENTOGRAHAM.COM


2702 SOUTH 1030 WEST SUITE 10 SOUTH SALT LAKE, UT 84020 (801) 270-9400 WWW.IGESINC.COM


DATE: 7/5/2018 1:41 PM

(801) 583-1295


328 W 200 S SUITE 102

SALT LAKE CITY, UT 84101












PROPANE TANK PIT TYPICAL DETAIL







DOWNSPOUT OUTFLOW CONNECTION





(213) 674-7238

WWW.TOMWISCOMBE.COM

POWDER MOUNTAIN HOUSE TOM BUTTGENBACH 8645 EASET COPPER CREST EDEN, UT 84310

5530 CORBIN AVE. SUITE 300

WWW.SHAMIMENGINEERING.COM

TARZANA, CA 91356

(818) 788-6778

STRUCTURAL ENGINEER: TOM WISCOMBE LOS ANGELES, CA 90057

LOS ANGELES, CA 90014 (213) 627-6687 WWW.NOUSENGINEERING.COM CIVIL ENGINEER: 5217 SOUTH STATE STREET MURRAY, UT 84107

(801) 743-1300

WWW.TALISMANCIVIL.COM

TALISMAN SINGINEERING CONSULTANTS INC.

GLENDALE, CA

WWW.ABRARI.COM

ARGENTO/GRAHAM 811 WEST 7TH STREET, 10TH FLOOR LOS ANGELES, CA 90017 (123) 456-7894 (323) 536-2578

WWW.ARGENTOGRAHAM.COM

2702 SOUTH 1030 WEST SUITE 10

(801) 270-9400

WWW.IGESINC.COM

SOUTH SALT LAKE, UT 84020

328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295

LIGHTING DESIGNER: KGM 328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295


WWW.KGMLIGHTING.COM





TCC PROJECT NUMBER: 18-009


DETAILS REVISIONS: BY: DATE: DATE: 07/05/2018 SCALE: DRAWN: SHEET:

DATE: 7/5/2018 1:29 PM









GRINDER PUMP STATION DETAIL



▼MECHANICAL PLUMBING XELECTRICAL XENERGY
□ACCESSIBILITY □ FIRE EST COAST CODE CONSULTANTS, IN



POWDER MOUNTAIN HOUSE TOM BUTTGEN BACH 8645 EASET COPPER CREST EDEN, UT 84310

TARZANA, CA 91356

WWW.SHAMIMENGINEERING.COM

(818) 788-6778

TOM WISCOMBE

LOS ANGELES, CA 90057

WWW.TOMWISCOMBE.COM

(213) 674-7238

LOS ANGELES, CA 90014 (213) 627-6687

WWW.NOUSENGINEERING.COM

STRUCTURAL ENGINEER: CIVIL ENGINEER: 5217 SOUTH STATE STREET MURRAY, UT 84107

(801) 743-1300

WWW.TALISMANCIVIL.COM

5530 CORBIN AVE. SUITE 300

TALISMAN SILIANTS SHAMIM ABRARI GLENDALE, CA

(123) 456-7894

WWW.ABRARI.COM

ARGENTO/GRAHAM 811 WEST 7TH STREET, 10TH FLOOR LOS ANGELES, CA 90017

(323) 536-2578

WWW.ARGENTOGRAHAM.COM

GES 2702 SOUTH 1030 WEST SUITE 10 SOUTH SALT LAKE, UT 84020


(801) 270-9400

WWW.IGESINC.COM

LDG salt lake city 328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295

LIGHTING DESIGNER: KGM 328 W 200 S SUITE 102 SALT LAKE CITY, UT 84101 (801) 583-1295

WWW.KGMLIGHTING.COM



TCC PROJECT NUMBER: 18-009

DETAILS REVISIONS: BY: DATE: DATE: 07/05/2018 DRAWN: SCALE: SHEET:

DATE: 7/5/2018 1:42 PM