

Perform washout of concrete trucks offsite or in designated concrete washout areas only. Do not wash out concrete trucks onto the ground, or into storm drains, open ditches, streets, or streams. Construction parking/traffic may not block the street without a permit (available from the Do not allow excess concrete to be dumped onsite, except in designated concrete washout areas.

(a) =

(b) =

(c) =

= (b)

(e) =

Contact

Engineering

ingineering

Building

Engineering

ingineering

Ingineering

Engineering

Concrete washout areas may be prefabricated concrete washout ainers, or self-installed structures (above-grade or below-grade). Prefabricated containers are most resistant to damage and protect against spills and leaks. Companies may offer delivery service and provide regular maintenance and disposal of solid and liquid waste.

Construction parking cannot be located within the R-O-W. No street side parking is allowed during the winter season, Nov. 15 thru April 15.

Roadside parking is not allowed from November 15 to Apr

Mud tracked out onto the street must be cleaned prior to the end of the work day

The construction site must be maintained in a neat manner. Trash and other debris may

Engineering Division)

not accumulate outside the dumpster.

Inspect daily for loss of gravel or sediment buildup.
Inspect adjacent roadway for sediment deposit and clean by sweeping or

shoveling. 3. Repair entrance and replace gravel as required to maintain control in

good working condition. 4. Expand stabilized area as required to accommodate traffic, and off site street parking and prevent erosion at driveway.

6"FOR COMMERCIAL 4" FOR RESIDENTIAL (INDIVIDUAL LOTS)

PLACE FILTER FABRIC BENEATH AGGREGATE IF PROJECT HAS A DURATION OF 3 MONTHS OR MORE.

1" TO 2-1/2" SIZE _

they are less prone to spills and leaks. Self-installed above-grade structures should only be used if excavation is not practical.

