


SITE PLAN GENERAL NOTES

- * DUST, MUD AND EROSION SHALL BE CONTROLLED BY WHATEVER MEANS NECESSARY, AND THE ROADWAY SHALL BE KEPT FREE OF MUD AND DEBRIS, AT ALL TIMES.
- * BUILDER/OWNER SHALL SECURE AN EXCAVATION PERMIT PRIOR TO DOING ANY WORK IN THE PUBLIC RIGHT-OF-WAY. TRAFFIC PLAN, BONDING AND INSURANCE WILL BE REQUIRED.
- * PROVIDE FINISH GRADING AWAY FROM THE HOUSE ON ALL SIDES AT A MINIMUM OF 6" IN. FIRST 10'-0" HORIZONTAL SLOPE IN LANDSCAPED AREAS. THEN MAINTAIN 2% MIN. HORIZONTAL SLOPE IN GRADE THEREAFTER TO APPROVED DRAINAGE AREAS.
- * IF RETAINING WALLS ARE REQUIRED, A PROFESSIONAL ENGINEER, CURRENTLY LICENSED IN UTAH, SHALL INSPECT AND APPROVE ANY RETAINING WALL THAT IS HIGHER THAN (4) FEET FROM BOTTOM FINISH GRADE TO TOP OF WALL, ONCE CONSTRUCTED.
- * PROVIDE ON SITE RETENTION OF ALL STORM WATER RUN OFF, BY WHATEVER MEANS NECESSARY DURING CONSTRUCTION.
- * SHOULD GROUND WATER BE INCURRED DURING EXCAYATION, A QUALIFIED SOILS ENGINEER SHALL BE RETAINED TO DESIGN AND APPROVE A CONTINUOUS FRENCH DRAIN AT FOUNDATION ON SITE.
- * MAINTAIN NATURAL EXISTING GRADE AT REAR AND SIDES OF LOT WHERE POSSIBLE TO RETAIN STORM WATER. NO RUNOFF ONTO ADJACENT PROPERTIES.



LOT #4
CHARLY'S ACRES SUBDIVISION
ADDRESS
HUNTSVILLE, UTAH

SITE PLAN

SCALE: |" = 50'-0"

RECORD

CAD TECH R.D.A

RELEASE 9/13/2

ENGINEER OF

51