

Sec 104-22-6.4 New Town Eden Area Building Design Standards

In addition to applicable standards in this chapter, the following standards apply to all buildings in the New Town Eden Area:


- (a) **Design theme.** All buildings shall have architectural styling and materials that implement agrarian-style architecture. Agrarian-style architecture shall incorporate at least two of the following four options:
- (1) Either a gable roof at a 6/12 or greater slope, a gambrel roof, or a monitor roof.

(2) An attached shed-roof at a 4/12 or greater slope that is not attached to the main roof structure.

(3) A clerestory or cupola.

(4) Gable-style dormer windows.
- (b) **Building form.** A building’s street-facing façade shall be designed to have a base, body, and varying roofline, each of varying design features and building material.
- (c) **Rooflines.** Rooflines shall be broken every 50 feet, with no less than a 12 inch shift between adjacent rooflines.
- (d) **Building massing.** The wall massing of building facades shall be broken at least every 40 feet with no less than a six inch shift in the plain of adjacent walls. Each street-facing building shall be designed and constructed to have a building base, building body, and varying building roofline, each having varying building materials or design techniques.
- (e) **Building material.** Building façade walls shall be finished with no less than two diverse types of material. The primary building material shall be wood siding or similar appearance. At least one of the building materials used on the building façade shall also be used on all other sides of the building.
- (1) Brick or stone may be used in place of wood if approved by the Land Use Authority.

(2) Metal siding may be used on the building's body, as long as the building's base is made of brick or stone, and as long as the metal siding is broken horizontally by brick or stone every twenty feet, and is treated to create a natural-appearing aged patina.
- (f) **Colors.** Muted earth-tone colors are required. No more than 70 percent of a building's facade shall be white.
- (g) **Examples.** Examples of generally acceptable architectural features are depicted in the following images. Any conflict between details in the images and regulations in this chapter shall be interpreted in favor of the regulations in the chapter.



**Editor's note:** This Section 104-22-6.3 was a part of Section 104-22-6.2, as provided in Ord #2022-20. Due to data size, 104-22-6.2 was pulled into four separate sections within Section 104-22-6. Those sections are 104-22-6.2, 104-22-6.3, 104-22-6.4, and 104-22-6.5.